



Proven product protection in a higher coverage rate.

**Foster® 40-50™
Mold-Resistant Coating**

Formulated on proven performance and years of experience, Foster® 40-50™ is the highest-quality, low-viscosity mold-resistant coating on the market today.

Foster 40-50 is a low-odor, easy-to-apply coating that leaves a clean, white film. It is formulated with EPA registered antimicrobial agents which provide protection against odor causing bacteria, mildew and mold growth on the product surface.



Versatile Surface Protection

Designed for use on a variety of surfaces, Foster 40-50 can be applied to:

- Bare wood*
- Wood studs*
- OSB*
- Drywall*
- Plywood*
- Painted surfaces*
- Wallboard*
- Masonry*
- Ceilings*
- Metal*





For Any Area

Tough and water resistant, Foster 40-50 provides residual protection of its surfaces in areas prone to the growth of mold, such as:

- Attic spaces
- Wall cavities
- Crawl spaces
- Wherever mold remediation has occurred
- Floor joists

Broad Applications

With its water-based formulation, Foster 40-50 is non-hazardous to apply and use in a wide range of applications:

- Commercial
- Residential
- Hospitals
- Schools

Competitively Superior

Foster 40-50 maintains long-term protection of its surface that is superior to alternative, lower-quality products available from competitive manufacturers.

Application: Low viscosity and good body allow easy hand application by brush or roller or with virtually any type of airless spray system

Coverage: 300 sq. ft./gallon

Dry Time: 1 hour at ambient

Color: White



Foster  TM
SPECIALTY CONSTRUCTION BRANDS, INC.

601 Campus Drive, Suite C7 | Arlington Heights, IL 60004
Phone: 800.231.9541 | Fax: 800.942.6856
www.fosterproducts.com